

Prestige

10 mm tongue/groove



Technical information	
Produced according to:	European parquet norm EN 13489 - 2017
Dimension:	10 x 70 x 470 mm
Toplayer:	about 3.5 mm
Construction:	2-layer construction; Hardwood toplayer and bottomlayer made of spruce Toplayer about 3.5 mm Bottomlayer 6.5 mm
Boards/ m² per carton:	40 pieces right-hand strips/ 40 pieces left-hand strips/ 2.63
Cartons/ m² per pallet:	36/ 94.68
Divided top layers per carton/ minimum length (mm):	2/ 235
Weight per carton/ pallet in kg:	14/ 522
Floor heating systems:	Very well suitable
Fire behavior ¹⁾:	Cfl-s1 and Dfl-s1 depending on wood specie and surface treatment.
Content of formaldehyd ²⁾:	E1
Content of pentachlorophenol (PCP) ²⁾:	no performance detected
Density kg/ m³ ²⁾:	about 600
Antislip performance:	Live Satin USRV 25 ²⁾ Live Matt USRV 29 ²⁾ Live Natural USRV 40 ²⁾
Abrasion resistance:	Live Satin 70/ 1100 ³⁾ Live Satin 100 ⁴⁾
Thermal conductivity ²⁾:	0.15 W/ (m·K)
Areal thermal resistance ⁵⁾:	0.067 m ² · K/ W



Toplayer: Hardwood
Bottomlayer: Spruce

DOP 4658



www.blauer-engel.de/uz176

CE
BOEN AS
EN 14342



¹⁾ according to DIN EN 13501-1, ²⁾ according to DIN 14342, ³⁾ according to ENV 13696,

⁴⁾ according to DIN 68861, ⁵⁾ according to EN 12524